

DH-IPC-F665P/N(-W)

1/3" CCD H.264 Network Camera



DH-IPC-F665P: 1/3" CCD, PAL video format, 25fps at D1/VGA, PoE

DH-IPC-F665P-W: 1/3" CCD, PAL video format, 25fps at D1/VGA, PoE, Wi-Fi




DH-IPC-F665N: 1/3" CCD, NTSC video format, 30fps at D1/VGA, PoE

DH-IPC-F665N-W: 1/3" CCD, NTSC video format, 30fps at D1/VGA, PoE, Wi-Fi

Features

- 1/3" SONY Super HAD CCD image sensor
- High-performance TI DaVinci series DSP
- H.264 video compression and JPEG image capture
- 25/30fps at D1/HD1/CIF/VGA resolution
- Dual encoding streams supported
- Multi-zone video detection and privacy masking
- 1 channel analogue video BNC output
- Support Alarm I/O, RS485 and RS232 interface
- Max 32GB Hot-swappable SD card for local storage
- Wi-Fi(802.11b/802.11g)
- PoE(IEEE802.3af)
- Built-in web server, NVR, DMSS & CMS

Dimensions (mm)



Specifications

Model		DH-IPC-F665P(-W)	DH-IPC-F665N(-W)
General	Processor	TI DaVinci Series DSP	
	Operating System	Embedded LINUX	
	Resource	Simultaneous remote monitoring, local recording and remote control	
	User Interface	WEB, CMS(DSS, PSS)	
Camera	Image Sensor	1/3" SONY Super HAD CCD	
	Effective Pixels	795(H)×596(V)	811(H)×508(V)
	Horizontal Resolution	540TVL(Color), B/W(600TVL)	
	Electronic Shutter	Auto/Manual, 1/50~1/10000s	Auto/Manual, 1/60~1/10000s
	Mini. Illumination	0.1LUX/F1.2	
	Signal Noise Ratio	>50dB	
	Gain Control	Auto	
	White Balance	Auto/Manual	
	Day/Night	Yes	
	Lens	CS-mount , Selectable	
	Lens Control	Zoom: Manual	
		Focus: Manual	
		Iris: Manual/Auto(DC Driver)	
Video	Video Compression	H.264	
	Resolution	D1(704×576) / HD1(352×576) / CIF(352×288) / QCIF(176×144) / VGA(640×480) / QVGA(320×240) / QQVGA(160×120)	D1(704×480) / HD1(352×480) / CIF(352×240) / QCIF176×128) / VGA(640×480) / QVGA(320×240) / QQVGA(160×120)
	Encoding Speed	Main Stream: D1/HD1/CIF/QCIF/VGA QVGA/QQVGA (1~25fps)	Main Stream: D1/HD1/CIF/QCIF/VGA QVGA/QQVGA (1~30fps)
		Extra Stream: D1/HD1/CIF/QCIF/VGA QVGA/QQVGA (1~25fps)	Extra Stream: D1/HD1/CIF/QCIF/VGA QVGA/QQVGA (1~30fps)
	Bit Rate	32K~4Mbps	
	Snapshot	Fastest 1fps JPEG capture	
	Video Format	PAL	NTSC
	Analogue Video Output	1 channel BNC(1.0Vp-p, 75Ω)	
Audio	Audio Compression	PCM(64Kbps) / G.711a(32Kbps) / AMR(10.2Kbps)	
	Input	1 channel 3.5mm Jack Mic in	
	Output	1 channel 3.5mm Jack Speak out	
Network	Ethernet	RJ-45 (10/100Base-T)	
	Wi-Fi	802.11b/802.11g, -W model supported	
	Network Functions	HTTP, TCP/IP, ICMP, RTSP, RTP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server	
	Remote Operation	Monitor, PTZ control, Playback, System setting, File download, Log information, Maintenance & Upgrade	
Auxiliary Interface	SD Card	Max 32GB, local storage	
	RS232	PC communication	
	RS485	PTZ control	
	Alarm	2 Input / 1 Output	
Environmental	Power Supply	DC 12V, PoE	
	Power Consumption	5W	
	Operating Environment	-10~+55°C, 10%~90%	
	Dimension	58mm×69mm×139mm	
	Weight	650g	